



	X	Y	Z	Ø	THREAD
UB -10	0.625	0.750	0.625	0.250	1/4-20 RHNC
UB -20	0.750	0.750	0.750	0.250	1/4-20 RHNC
UB -30	0.875	0.750	0.875	0.250	1/4-20 RHNC
UB -40	1.105	0.750	1.105	0.250	1/4-20 RHNC
UB -50	1.163	0.750	1.163	0.250	1/4-20 RHNC
UB -60	1.375	0.750	1.375	0.250	1/4-20 RHNC
UB -70	1.500	0.750	1.500	0.250	1/4-20 RHNC
UB -80	1.600	0.750	1.600	0.250	1/4-20 RHNC
UB -90	1.900	0.750	1.900	0.250	1/4-20 RHNC
UB -100	2.000	0.750	2.000	0.250	1/4-20 RHNC
UB -110	2.375	0.750	2.375	0.313	5/16-18 RHNC
UB -120	2.500	0.750	2.500	0.313	5/16-18 RHNC
UB -130	2.875	0.750	2.875	0.313	5/16-18 RHNC
UB -140	3.000	0.750	3.000	0.313	5/16-18 RHNC
UB -150	3.500	0.750	3.500	0.313	5/16-18 RHNC
UB -160	4.000	0.750	4.000	0.313	5/16-18 RHNC
UB -170	4.500	0.750	4.500	0.313	5/16-18 RHNC

TOLERANCES  unless otherwise specified ANGLES = ± 1° FRACTIONS = ± 1/32 DECIMALS XX = ± .01 XXX = ± .005	Drawn by: DB	Aprvd by: JT	Material: T-3040SS	Date: 1-8-15
	<b>Food Grade Solutions</b> (559) 834-1219 2030 S. Golden State Blvd. #206 PO Box 69, Fowler, CA 93625 www.foodgradesolutions.com		Drawing Title: U-Bolts	Drawing Number: F20150111-A8